


ON DEMAND SEAL PLATE SIGNIFICANTLY REDUCES ENERGY CONSUMPTION

FEATURES

- New Feature - Square Edged Hot Rod Cuts Film with Ease
- Cradle Mount for Film Saves Labor
- Fixed Distance Photo Eye Detects All Tray Colors
- Two Color LED light indicates Yellow when Seal Plate is Heating, and Red when Seal Plate Reaches Sealing Temperature
- Circuit Breakers have replaced fuses for Fast, Easy Reset, and Low Maintenance
- On-Demand Microprocessor Controlled Seal Plate Significantly Reduces Power Consumption by 80%
- Rigid Aluminum and Stainless Steel Construction
- Supplied with a Replaceable Non-Stick Cover to Maintain a Hygienic Sealing Surface
- Local Utility Rebates may be Available



MODEL SPECS

MODEL	700ES - C
FILM MOUNT	Cradle System
FILM CAPACITY	20" Maximum Roll Width, 8" Maximum Roll Diameter
SEAL PLATE	6" x 15"
OVERALL DIMENSIONS	24.75" D, 23" W, 9" H (63 D, 59 W, 23 H cm)
ELECTRICAL SPECIFICATIONS	 115 Volt, 60Hz, 132 Watts
WEIGHT	28 lbs. (13kg)
OTHER FEATURES	No Assembly Required, Quick Film Changeover
COMPARABLE TO	600A

