

Step-Saver® Systems Economical and Efficient



| Controller | bPro | Impact S | Impact M | UC-PW |
|-------------------------------------|--|------------------------------|------------------------------|------------------------------|
| Keyboard | Tactile | Tactile/Touch | Touchscreen | Touchscreen |
| Programmable Presets | 140 | 1440 | 1440 | Unlimited |
| COOL Capability | Yes | Yes | Yes | Yes |
| NutriFacts/ SafeHandling | Yes | Yes | Yes | Yes |
| Display | Monochrome LCD | Monochrome LCD | Color LCD | Color LCD |
| Operating Range | 32°F to 104°F 0°C to 40°C | 32°F to 104°F 0°C to 40°C | 41°F to 104°F 5°C to 40°C | 41°F to 104°F 5°C to 40°C |
| Label Capacity | Standard | Standard | Standard | High Capacity |
| Label Sizes | 1" to 7.9" long and 1.6" (40 mm) to 3.4" (86 mm) wide | | | |
| Controller Construction | Die cast metal base, plastic case | Stainless steel enclosure | Die cast aluminum | Epoxy Coated Steel |
| Dimensions | 46" (116.9 cm) H x 50" (127 cm) W x 33" (83.8 cm) D | | | |
| Film Capacity | Two rolls up to 20" (50.8 cm) wide | | | |
| Film Type | PVC Stretch | | | |
| Bottom Seal | Thermostat Controlled Sealing Plate | | | |
| Film Cutting | Thermostat Controlled Low Temp Rod | | | |
| Step-Saver® Power | 115 VAC, 60 Hz, 10A, 625 watts (excluding scale and printer) | | | |
| Step-Saver® Construction | Stainless Steel | | | |
| Scale Capacity | 50 x 0.01 lb (20 x 0.005 kg) | | | |
| Options | Stainless steel 12" X 24" platter shelf (left-right), label dispenser rack | | | |



Manufactured in a facility that is ISO9001 certified.



Mettler-Toledo, LLC
1900 Polaris Parkway
Columbus, Ohio 43240
TEL. (800) 523-5123
(614) 438-4511

METTLER TOLEDO

