Hollymatic

DOUBLE CHAMBER & FLOOR MODEL VACUUM PACKAGING MACHINES

All Stainless Steel Construction and High Quality Busch Vacuum Pumps

Hollymatic Double Chamber and Floor Model Units are designed and built for the processor, with state-of-the-art vacuum packaging technology and heavy duty reinforced chambers.

Innovative sensor controls provide features that facilitate production and allow for the very best appearance of finished packages.

- ▶ Red Meat Program
- ▶ 10 Program Storage (Sensor Controlled)
- ▶ Soft Aeration
- ▶ Pump Conditioning Program
- ▶ Diagnostic Gate System Check

OPTIONS

- ▶ Gas Flush
- ▶ ACS (Advanced Control System) (20 Programs)
- ▶ Printer Labeling with ACS
- ▶ Liquid Control through Boiling Point Detection
- ▶ Cut-off Seal
- ▶ High Lid (Polar 2-85)

MARLIN 52

POLAR 2-75

POLAR 2-85

c ETL us LISTED Intertek

ETL SANITATION LISTED Intertek

CE

BUSCH

Hollymatic®

FOOD PROCESSING EQUIPMENT SINCE 1937

Hollymatic Vacuum Packaging Machines

Marlin 52

SPECIFICATIONS:

Useable Chamber Size:	20.5" x 19.7" x 7.9"
Seal Bar L-R:	2 @ 20.5"
Distance between Seal Bars:	19.7"
Seal Bar Front:	1 @ 23.6" (optional)
Seal Type:	Double Seal
Vacuum Pump:	63 m^3/hr
Digital Controls:	Touch pad
Electrical:	230 volt / 60 Hz. / 3 ph
Overall Dimensions:	28" x 27.4" x 40.6"
Net Weight:	364 lbs.

Polar 2-75

SPECIFICATIONS:

Useable Chamber Size:	33" x 20.8" x 9.8"
Seal Bar L-R:	2 @ 33"
Distance between Seal Bars:	20.8"
Seal Bar F-B:	2 @ 24.4" (optional)
Distance between Seal Bars:	29.5"
Seal Type:	Double Seal
Vacuum Pump:	192 m^3/hr
Digital Controls:	Touch pad
Electrical:	230 volt / 60 Hz. / 3 ph
Overall Dimensions:	61" x 45.3" x 46.5"
Net Weight:	1,183 lbs.

Polar 2-85

SPECIFICATIONS:

Useable Chamber Size:	32.6" x 33.1" x 10"
Seal Bar:	2 @ 33"/chamber
Distance between Seal Bars:	32.6" F-B
Seal Type:	Double Seal
Vacuum Pump:	360 m^3/hr
Digital Controls:	Touch pad
Electrical:	230 volt / 60 Hz. / 3 ph
Overall Dimensions:	78" x 48.5" x 46.5"
Net Weight:	1,510 lbs.