

SHRINK TUNNEL

MODEL: T4832



Specification Sheet

FEATURES

TUNNEL CHAMBER

- Efficient Max Air Tunnel Triples the Airflow and evenly wraps air around package
- High Velocity Air Flow
- Three Heat Zones



Model T4832

CONVEYOR FEATURES

- 5/8" Diameter Live/Dead Rollers with 2" Spacing
- High Temperature Glass Filled Nylon Conveyor Standard
- One Quarter Horsepower Motor With Adjustable Conveyor Speeds Of Up To 35 Feet Per Minute

OTHER FEATURES

- Heavy Gauge Adjustable Height Console With Levelers And 3" Casters
- Stainless Steel Model Available
- Two Year Warranty

MODEL SPECS

INSIDE TUNNEL DIMENSIONS	48" L, 32" W, 12" H (122 cm L, 81 cm W, 30 cm H)
CONVEYOR	Variable Speed, Live/Dead Silicone Covered Rollers with 2" Spacing
CONVEYOR SPEED	0 - 35 ft./min. (10.7 m./min.)
OVERALL DIMENSIONS	74" L, 41" W, 58" H (189 cm L, 104 cm W, 148 cm H)
POWER REQUIREMENTS	208~240 Volts, 65 Amps Three Phase
WATTAGE	18,000 Watts
WEIGHT	860 lbs. (391 kg)

AVAILABLE OPTIONS

- Stainless Steel Construction (T4832S)
- Stainless Steel Wire Mesh Belt Conveyor
- Non-stick Mesh Belt Conveyor
- 16" High Tunnel Opening
- Reverse Flow



