



# 8150 UTENSIL WASHER

## Technical specification



### Rinse

Temperature: 183° F (84° C)  
Rinse Time: 25 seconds

### Standard Features

- Automatic open and close of hood
- 4 sided moving wash frame
- Load and unload from 3 sides
- Self cleaning program
- Adjustable wash temperature
- Hi and low wash programs
- 3 preset programs 2, 4, 6 min.
- 2 easily accessible filters
- 2-3.0 kW wash pumps
- 21 psi of pressure at the nozzle
- Automatic start
- Drain pump
- Soap dosage pump

### Optional features

- Chemical sanitizer pump
- Integrated faucet
- External pre-wash hose
- Side table
- Pre-wash table with sink

### General specification

Wash tank capacity	44 gal
Wash area	
H x W x D	37x52x31 inch
Overall dimensions	
H x W x D	76x67x42 inch
H x W x D with hood open	101x67x42 inch
Weight Shipping	770 lbs
Weight installed (Including Water)	1144lbs
Water connection, flexible	8 feet
Electrical connection	8 feet
Vinyl brush daily maintenance	1 piece

### POWER / CONNECTIONS

#### Electrical

Electrical connection	3N 60Hz 240/480, PE
Effect (2x9.0 kW)	Max 24.5 kW
(2x6.0 kW)	18.5 kW

#### Heating Elements

Wash tank	1x6.0 kW
Rinse Tank	2x7.5 kW

Amperage	230 volt	59 amps
----------	----------	---------

Wash pump motor horsepower	2 x 3.0 kW
----------------------------	------------

#### Water

Connection	½ inch.
Pressure	45 to 60 psi
Consumption per cycle	2 gallons
Temperature: (minimum)	122° F (50 C°)

#### Drain

Drain dimension:	1 ½ inch
------------------	----------



ALL SPECIFICATION SUBJECT TO CHANGE WITHOUT NOTICE

SMARTER THINKING – SMARTER SOLUTIONS

8064 Chivvis Drive St. Louis, MO 63123 Fax (314) 353-6655 (877) 677-7761 [www.maincausa.com](http://www.maincausa.com)