



8160 UTENSIL WASHER

Technical specification



Standard Features

- Automatic roll door
- 4 sided moving wash frame
- Self cleaning program
- Adjustable wash temperature
- Hi and low wash programs
- 3 preset programs 2, 4, 6 min.
- 2 easily accessible filters
- 2-3.0 kW wash pumps
- 21 psi of pressure at the nozzle
- Automatic start
- Drain pump

Optional features

- Soap dosage pump
- Chemical sanitizer pump
- Integrated faucet
- External pre-wash hose
- Side table
- Pre-wash table with sink

General specification

Wash tank capacity	44 gal
Wash area	
H x W x D	37x52x31 inch
Overall dimensions	
H x W x D	76x67x42 inch
H x W x D with hood open	84x67x42 inch
Weight Shipping	770 lbs
Weight installed	1144lbs
Water connection, flexible	8 feet
Electrical connection	8 feet
Vinyl brush daily maintenance	1 piece

POWER / CONNECTIONS

Electrical

Electrical connection	3N 60Hz 240/480, PE
Effect (2x9.0 kW)	Max 24.5 kW
(2x6.0 kW)	18.5 kW

Heating Elements

Wash tank	1x6.0 kW
Rinse Tank	2x7.5 kW
Option Rinse Tank	2x9.0 kW

Fuses

240 volt	Max 63 amp
480 volt	Max 50 amp

Motor safety

Wash pump motor horsepower	Yes
	2 x 3.0 kW

Water

Connection	½ inch.
Pressure	45 to 60 psi
Consumption per cycle	4.25 gallons
Temperature: (minimum)	122° F (50 C°)

Drain

Drain dimension:	1 ½ inch
------------------	----------

Rinse

Temperature:	183° F (84° C)
Rinse Time:	25 seconds



8064 Chivvis Drive
St. Louis, MO 63123
Fax (314) 353-6600
(877) 677-7761
(314) 351-4677

www.maincausa.com