



9110 Utensil Washer

Technical Specifications



JEROS 9110 Features:

- ✓ Top & Bottom Spray Bars
- ✓ 3-side Open Design
- ✓ Ergonomic Loading and Unloading
- ✓ 3 Programmable Wash Cycle Buttons
- ✓ Environmentally Friendly
- ✓ Built-in Soap Dosing Systems
- ✓ Self-contained Wash Water Heating Elements
- ✓ Adjustable Wash Temperature
- ✓ Separate Sanitary Rinse Plumbing
- ✓ Built-in 184 °F Rinse
- ✓ Adjustable Rinse Temperature
- ✓ "Rinse Sense" Guaranteed Sanitation
- ✓ Minimal Space Requirement
- ✓ Automatic Start
- ✓ Automatic Drain and Rinse System
- ✓ 17 PSI of Pressure at the Nozzle
- ✓ Easily Accessible Waste Collection Basket
- ✓ High and Low Pressure Wash Program
- ✓ NSF Approved

POWER / UTILITIES

Electrical:

Electrical Connection	3 ph, 60Hz, 230/480 volt
Total Amperage	16 amp (at 230 v)
Heating Elements:	
Wash Tank	1 x 4.5 kW
Rinse Tank	2 x 6.0 kW
Wash Pump Motor	1 HP, 5.0 kW

Water:

Connection	½" NPT Flex
Input Pressure Required	45 to 60 psi
Water Consumption per Cycle	1 gallon (3.8 liters)
Input Temperature (minimum)	122 °F (50 °C)
Rinse Temperature	180° - 203 °F (82° - 95 °C)
Rinse Time	20 – 40 seconds

Drain:

Drain Diameter	1-1/2" (8' Flex drain incl'd)
----------------	-------------------------------

Options:

- Chemical Sanitation Pump
- Integrated Faucet
- Pre-spray Nozzle and Hose
- External Pre-wash Hose

General Specifications:

Wash Tank Capacity	13.4 gallons (50.72 liters)
Wash Area	27" W x 25" D x 23" H
Overall Dimensions	
Hood Closed	33" W x 33.5" D x 64" H
Hood Open	33" W x 33.5" D x 83" H
Includes Cord (no plug)	

Wash, Rinse and Sanitize in as little as 3 minutes... "If it FITS INSIDE – It's SANITIZED"

8064 Chivvis Drive St. Louis, MO 63123 Fax (314) 353-6655 (877) 677-7761

For more information visit www.maincausa.com and www.jeros.com

