



9117 UTENSIL WASHER

Technical specification



Rinse Temperature: 183° F (84° C)
Rinse Time: 25 seconds

Standard Features

- 4 sided moving wash frame
- Load and unload from 3 sides
- Self cleaning program
- Adjustable wash temperature
- Hi and low wash programs
- 3 preset programs 2, 4, 6 min.
- 2 easily accessible filters
- 1-5 kW wash pumps
- 21 psi of pressure at the nozzle
- Automatic start
- Drain pump
- Automatic Soap Dosage Pump

Optional features

- Automatic hood opener
- Chemical sanitizer pump
- Integrated faucet
- External pre-wash hose
- Side table
- Pre-wash table with sink

General specification

Wash tank capacity	20 gallons
Wash area	
H x W x D	25x31x25 inch
Overall dimensions	
H x W x D	64x39x29 inch
H x W x D with hood open	82x39x29 inch
Weight Shipping	435 lbs
Weight installed	654 lbs
Water connection, flexible	8 feet
Electrical connection	8 feet

POWER / CONNECTIONS

Electrical

Electrical connection	3N 60Hz 240/480, PE
Effect	16.5 kW
Heating Elements	

Wash tank	1x4.5 kW
Rinse Tank	2x6.0 kW

Fuses

240 volt	Max 32 amp
480 volt	Max 32 amp

Motor safety

Yes

Wash pump motor horsepower

1-5.0 kW

Water

Connection	½ inch.
Pressure	45 to 60 psi
Consumption per cycle	1.1 gallons
Temperature: (minimum)	122° F (50 C°)

Drain

Drain dimension: 1 ½ inch



ALL SPECIFICATION SUBJECT TO CHANGE WITHOUT NOTICE

SMARTER THINKING – SMARTER SOLUTIONS

8064 Chivvis Drive St. Louis, MO 63123 Fax (314) 353-6655 (877) 677-7761 www.maincausa.com