



9120 UTENSIL WASHER

Technical specification



Rinse Temperature 183° F (84° C)
Rinse Time: 25 seconds

Standard Features

- 4 sided moving wash frame
- Load and unload from 3 sides
- Self cleaning program
- Adjustable wash temperature
- Hi and low wash programs
- 3 preset programs 2, 4, 6 min.
- 2 easily accessible filters
- 1-2.0, 1-2.7 kW wash pumps
- 21 psi of pressure at the nozzle
- Automatic start
- Drain pump
- 2 tray racks

Optional features

- Automatic hood opener
- Soap dosage pump
- Chemical sanitizer pump
- Integrated faucet
- External pre-wash hose
- Side table
- Pre-wash table with sink

General specification

Wash tank capacity	25 gallons
Wash area	
H x W x D	25x39x25 inch
Overall dimensions	
H x W x D	64x46x29 inch
H x W x D with hood open	82x46x29 inch
Weight Shipping	495 lbs
Weight installed	704 lbs
Water connection, flexible	8 feet
Electrical connection	8 feet
Vinyl brush, daily maintenance	1 piece

POWER / CONNECTIONS

Electrical

Electrical connection	3N 60Hz 208/230 PE
Effect	16.5 kW

Heating Elements

Wash tank	1x4.5 kW
Rinse Tank	2x6.0 kW

Fuses

208/230/240 volt	Max 50 amp
480 volt	Max 50 amp

Motor safety

Yes

Wash pump motor horsepower

2-2.0 kW

Water

Connection	½ inch.
Pressure	45 to 60 psi
Consumption per cycle	2.1 gallons
Temperature: (minimum)	122° F (50 C°)

Drain

Drain dimension: 1 ½ inch



ALL SPECIFICATION SUBJECT TO CHANGE WITHOUT NOTICE

SMARTER THINKING – SMARTER SOLUTIONS

8064 Chivvis Drive

St. Louis, MO 63123

Fax (314) 353-6655

(877) 677-7761

www.maincausa.com