



Rinse Temperature: 183° F (84° C)
Rinse Time: 25 seconds

Standard Features

- 4 sided moving wash frame
- Load and unload from 3 sides
- Self cleaning program
- Adjustable wash temperature
- Hi and low wash programs
- 3 preset programs 2, 4, 6 min.
- 2 easily accessible filters
- 2-2.7 kW wash pumps
- 21 psi of pressure at the nozzle
- Automatic start
- Drain pump
- Soap dosage pump

Optional features

- Automatic hood opener
- Chemical sanitizer pump
- Integrated faucet
- External pre-wash hose
- Side table
- Pre-wash table with sink

General specification

Wash tank capacity	33 gallons
Wash area	
H x W x D	25x50x27 inch
Overall dimensions	
H x W x D	64x57x31 inch
H x W x D with hood open	82x57x31 inch
Weight Shipping	550 lbs
Weight installed (Including Water)	825 lbs
Water connection, flexible	8 feet
Electrical connection	8 feet
Vinyl brush, daily maintenance	1 piece

POWER / CONNECTIONS

Electrical

Electrical connection	3N 60Hz 240/480, PE
Effect	16.5 kW
Heating Elements	
Wash tank	1x4.5 kW
Rinse Tank	2x6.0 kW
Fuses	
240 volt	Max 50 amp
480 volt	Max 50 amp
Wash pump motor horsepower	2-2.7 kW

Water

Connection	½ inch.
Pressure	45 to 60 psi
Consumption per cycle	1.5 gallons
Temperature: (minimum)	122° F (50 C°)

Drain

Drain dimension:	1 ½ inch
------------------	----------



ALL SPECIFICATION SUBJECT TO CHANGE WITHOUT NOTICE

SMARTER THINKING – SMARTER SOLUTIONS

8064 Chivvis Drive St. Louis, MO 63123 Fax (314) 353-6655 (877) 677-7761 www.maincausa.com